

HALLIDAY & BAILLIE KEY LOCK SLIDING SYSTEM FOR TIMBER SLIDERS

ORDER CODES:

HB630 - MATT SATIN SILVER (marine zinc coated)*

HB630B - OILED DARK BRONZE

HB630C - MIRROR CHROME

HB630N - NICKEL (stainless steel look)

The new HB630 has a key both sides with a flush pull & snib both sides. For variations to this see codes HB632, HB633 & HB638, 636,637 (see following fact sheets)

The absolute minimum the slider thickness can be is 37mm-40mm.

A cylinder is supplied with each system that will cater to a MAX of 42mm in slider thickness. If your slider is 42+ then the cylinder will sit inside the outer faceplate please then be aware of this when specifying & then purchasing.

With the length of the key cylinders available on the market, a slider thickness of 40, 60 or 70mm will make this system completely flush and therefore allow the slider to either travel into a cavity wall or pass over other panels, moving or fixed without the need to place a stop in your tracks. This then means you get the full door opening.

(Please note the 40mm cylinder is a 3pin system & cannot be keyed to 5 or 6pin key systems)

The ideal slider thickness is 40mm, however we do provide a longer extended spindle inside each system for any further door thickness. You simply cut this down to fit your slider. Please read cylinder notes above.

*** Treated for outdoor coastal use with normal expected maintenance programme to be in place.***

Product feature! - you can open and close & latch your slider without using the key!. When you want to deadlock the door, you simply key it so that the snib is locked, take out your key and voila!

Image below is inside view

Snib the lock to latch the slider, pull down to unlatch. To deadlock and leave your property use key to lock the snib from moving.

Image below is outside view

Snib the lock to latch the slider pull down to unlatch. To deadlock and leave your property use key to lock the snib from moving.



Lock faceplate length is 213mm

Lock body depth is 73mm

Centre to Key & snib is 55mm

Minimum Stile width for this lock is 90mm to avoid hitting the glazing

As the centre measurement is 55mm the ideal stile width is 110mm

Fig.1 Lockset Dimension Drawing

