

Components for HB 2220 Glass Fix Kit

- (1.) Brass D Pull (sold seperately in 300mm, 600mm & 1200mm lengths and multiple bar sizes)
- 2. Brass rose (these are supplied with the D Pull and installation is optional depending on your aesthetic)
- (3.) MBolt Fixing insert
- 4.) M Threaded rod with hex end (M6 for 16mm rod and M8 for 19mm rod)
- (5.) Grommet
- (6.) Brass cap (threaded)
- 7.) HB 2260 Brass Knob (threaded)
- 8. Grub screw

Installation instructions

- 1. Insert MBolt fixing insert (3) into both ends of D Pull and secure with grub screws provided in the pull.
- 2. Screw threaded rods (4) into MBolt fixing insert.
- 3. Place grommets (5) into pre drilled 11mm holes on both sides of the glass door. If brass roses are being used these need to be slid over the threaded rods before placing through the glass.
- 4. Insert D Pull with threaded rods through grommets. Screw brass cap HB 2260 Brass Knob onto threaded rods (the HB 2260 can be installed to either top or bottom depending on use).

Designed and manufactured in New Zealand. For more information, installation templates, and measured drawings of this product and others please visit: www.hallidaybaillie.com or contact your authorized Halliday + Baillie dealer. All information subject to change.

<u>hallid</u>ay baillie

HB 2220 Glass Fix Kit

For HB 2200 Series Brass D Pulls


HB 2220 16mm Glass : Glass Fix Kit, HB 2200 Series 16mm Rod HB 2220 19mm Glass : Glass Fix Kit, HB 2200 Series 19mm Rod


The HB 2220 Glass Fix Kit is designed for installation of the HB 2200 Series D Pulls on frameless glass doors. Kits come with all parts required other than the D Pull itself.

Kits for other fixings methods including single side fix into timber doors, and back to back and through fixings are also available.

(Please check with your H+B representative, not all finishes available in all regions.)

AB : Aged Brass SB : Satin Brass PB : Polished Brass KC : Black Chrome







Polyethylene Grommet