

HB2220 SERIES FIX KIT RODS

Fixing sets for the Halliday + Baillie D Pulls are designed for multiple door types and thicknesses. Across the range we have sets that can accommodate single side (face) fix, back to back fix, glass back to back fix, glass single side fix, aluminum single side fix, and through fix options. All sets ship with solid brass roses which are optional for installation. For use with soft wood doors like cedar and pine we recommend installation with the rose, particularly as the pull length increases. Installing with the rose helps limit deflection, and potential 'dig' of the sharp edge of the pull into a soft timber door.

Sets also accommodate a wide range of door thicknesses. Different threaded rods can be ordered, therefore providing door thicknesses for order is recommended.

We have four standard threaded rod sizes in stock and minimum and maximum door thicknesses for each are below. Each rod length can accommodate a range of thicknesses depending on how far the rod is inserted into the fixing adaptor as per the diagram to the left. We recommend at least 8mm (half the length of the adaptor) of rod is inserted on each side to ensure suitable connection. For doors smaller or larger than the thicknesses below, please contact your local Halliday + Baillie representative for a customised solution.

40mm Rod : Doors between 10mm and 25mm (used in the glass door sets)
 50mm Rod : Doors between 20mm and 35mm
 60mm Rod : Doors between 30mm and 45mm
 70mm Rod : Doors between 40mm and 55mm
 90mm Rod : Doors between 55mm and 75mm

Doors over 75mm thick will require a custom length, Rod.

Fixing sets using these rods are available in the finishes below.

AB : Aged Brass SB : Satin Brass
 PB : Polished Brass KC : Black Chrome

