



Rod half screwed into adaptor

Components for HB 2220 & HB 2330 Fix Sets

(1) Brass rose (these are supplied with the fixing set in a matching finish and installation is optional depending on your aesthetic)

) M Bolt fixing rod

.) Stainless steel fix adaptor

Designed and manufactured in New Zealand. For more information, installation templates, and measured drawings of this product and others please visit : www.hallidaybaillie.com or contact your authorized Halliday + Baillie dealer. All information subject to change.

© 2023 v1 Halliday + Baillie Ltd.

<u>hallid</u>ay baillie

HB 2220 & HB 2330 Series Fix Kit Rods

Fixing sets for the Halliday + Baillie D Pulls are designed for multiple door types and thicknesses. Across the range we have sets that can accommodate single side (face) fix, back to back fix, glass back to back fix, glass single side fix, aluminum single side fix, and through fix options. All sets ship with solid brass roses which are optional for installation. For use with soft wood doors like cedar and pine we recommend installation with the rose, particularly as the pull length increases. Installing with the rose helps limit deflection, and potential 'dig' of the sharp edge of the pull into a soft timber door.

Sets also accommodate a wide range of door thicknesses. Different threaded rods can be ordered, therefore providing door thicknesses for order is recommended.

We have four standard threaded rod sizes in stock and minimum and maximum door thicknesses for each are below. Each rod length can accommodate a range of thicknesses depending on how far the rod is inserted into the fixing adaptor as per the diagram to the left. We recommend at least 8mm (half the length of the adaptor) of rod is inserted on each side to ensure suitable connection. For doors smaller or larger than the thicknesses below, please contact your local Halliday + Baillie representative for a customised solution.

 $40 \mathrm{mm}\ \mathrm{Rod}$: Doors between $8 \mathrm{mm}\ \mathrm{and}\ 24 \mathrm{mm}\ (\mathrm{used}\ \mathrm{in}\ \mathrm{the}\ \mathrm{glass}\ \mathrm{door}\ \mathrm{sets})$

50mm Rod : Doors between 18mm and 34mm 60mm Rod : Doors between 28mm and 44mm 90mm Rod : Doors between 58mm and 75mm

Please note all finishes below are unlacquered:AB : Aged BrassSB : Satin BrassPB : Polished BrassKC : Black Chrome